

Insulation shell for valve R5..

- only for non-condensing applications
- easy mounting thanks to velcro strip
- can also be mounted/dismounted subsequently



Picture may differ from product

### Type Overview

Type	DN	Suitable for	Weight
EXT-OC-ZR515	15	R5.. DN 15	0.045 kg
EXT-OC-ZR520	20	R5.. DN 20	0.060 kg
EXT-OC-ZR525	25	R5.. DN 25	0.056 kg
EXT-OC-ZR532	32	R5.. DN 32	0.096 kg
EXT-OC-ZR540	40	R5.. DN 40	0.11 kg
EXT-OC-ZR550	50	R5.. DN 50	0.13 kg

### Technical data

<b>Functional data</b>	Thermal conductivity	0.035 W/mK
<b>Materials</b>	Used materials	Polyethylen foam (PE-3015 acc. EN 12667:2001 / EN 12664:2001)

### Safety notes



- This accessory has been designed for use in stationary heating, ventilation and air-conditioning systems and must not be used outside the specified field of application, especially in aircraft or in any other airborne means of transport.
- Only authorised specialists may carry out installation. All applicable legal or institutional installation regulations must be complied with during installation.
- The accessory may not be disposed of as household refuse. All locally valid regulations and requirements must be observed.