

Damper actuator for adjusting dampers in technical building installations

- Air damper size up to approx. 1 m<sup>2</sup>
- Torque motor 5 Nm
- Nominal voltage AC 100...240 V
- Control Open/close, 3-point
- Running time motor 35 s
- Mechanical interface Form fit 8x8 mm



Picture may differ from product

## Technical data

Electrical data	
	Nominal voltage
	AC 100...240 V
	Nominal voltage frequency
	50/60 Hz
	Nominal voltage range
	AC 85...265 V
	Power consumption in operation
	2 W
	Power consumption in rest position
	0.5 W
	Power consumption for wire sizing
	4 VA
	Connection supply / control
	Cable 1 m, 3x 0.75 mm <sup>2</sup>
	Parallel operation
	Yes (note the performance data)
Functional data	
	Torque motor
	5 Nm
	Direction of motion motor
	selectable with switch 0 (ccw rotation) / 1 (cw rotation)
	Manual override
	with push-button, can be locked
	Angle of rotation
	Max. 95°
	Angle of rotation note
	can be limited on both sides with adjustable mechanical end stops
	Running time motor
	35 s / 90°
	Sound power level, motor
	45 dB(A)
	Mechanical interface
	Form fit 8x8 mm
	Position indication
	Mechanical, pluggable
Safety data	
	Protection class IEC/EN
	II, reinforced insulation
	Protection class UL
	II, reinforced insulation
	Degree of protection IEC/EN
	IP54
	Degree of protection NEMA/UL
	NEMA 2
	Housing
	UL Enclosure Type 2
	EMC
	CE according to 2014/30/EU
	Low voltage directive
	CE according to 2014/35/EU
	Certification IEC/EN
	IEC/EN 60730-1 and IEC/EN 60730-2-14
	UL Approval
	cULus according to UL60730-1A, UL60730-2-14 and CAN/CSA E60730-1
	The UL marking on the actuator depends on the production site, the device is UL-compliant in any case
	Hygiene test
	According to VDI 6022 Part 1 / SWKI VA 104-01, cleanable and disinfectable, low emission
	Type of action
	Type 1

<b>Safety data</b>	Rated impulse voltage supply / control	2.5 kV
Pollution degree	3	
Ambient humidity	Max. 95% RH, non-condensing	
Ambient temperature	-30...50°C [-22...122°F]	
Storage temperature	-40...80°C [-40...176°F]	
Servicing	maintenance-free	
<b>Weight</b>	Weight	0.42 kg

## Safety notes



- This device has been designed for use in stationary heating, ventilation and air-conditioning systems and must not be used outside the specified field of application, especially in aircraft or in any other airborne means of transport.
- Outdoor application: only possible in case that no (sea) water, snow, ice, insolation or aggressive gases interfere directly with the device and that it is ensured that the ambient conditions remain within the thresholds according to the data sheet at any time.
- Caution: Mains voltage!
- Only authorised specialists may carry out installation. All applicable legal or institutional installation regulations must be complied with during installation.
- The device may only be opened at the manufacturer's site. It does not contain any parts that can be replaced or repaired by the user.
- Cables must not be removed from the device.
- To calculate the torque required, the specifications supplied by the damper manufacturers concerning the cross-section and the design, as well as the installation situation and the ventilation conditions must be observed.
- The device contains electrical and electronic components and must not be disposed of as household refuse. All locally valid regulations and requirements must be observed.

## Product features

<b>Simple direct mounting</b>	Simple direct mounting on the damper shaft with form-fit hollow shaft. For screw fitting to the application the actuator is supplied with two fastening clips, one on each short side.
<b>Manual override</b>	Manual override with push-button possible (the gear train is disengaged for as long as the button is pressed or remains locked).
<b>Adjustable angle of rotation</b>	Adjustable angle of rotation with mechanical end stops.
<b>High functional reliability</b>	The actuator is overload protected, requires no limit switches and automatically stops when the end stop is reached.

## Accessories

Electrical accessories	Description	Type
Auxiliary switch 1x SPDT add-on		S1A
Auxiliary switch 2x SPDT add-on		S2A
Feedback potentiometer 140 Ω add-on		P140A
Feedback potentiometer 1 kΩ add-on		P1000A
Feedback potentiometer 10 kΩ add-on		P10000A
Mechanical accessories	Description	Type
Shaft extension 170 mm ø10 mm for damper shaft ø6...16 mm		AV6-20
Shaft clamp, for damper shafts L 13...30 mm, clamping range ø8...12 mm, incl. anti-rotation mechanism 180 mm and 2 screws		K5A
Anti-rotation mechanism 180 mm, Multipack 20 pcs.		Z-ARS180
Form fit insert 8x8 mm, Multipack 20 pcs.		ZF8-LMA
Form fit insert 10x10 mm, Multipack 20 pcs.		ZF10-LMA

## Accessories

Description	Type
Form fit insert 12x12 mm, Multipack 20 pcs.	ZF12-LMA
Form fit insert 8x8 mm, with angle of rotation limiter and position indicator, Multipack 20 pcs.	ZFRL8-LMA
Form fit insert 10x10 mm, with angle of rotation limiter and position indicator, Multipack 20 pcs.	ZFRL10-LMA
Form fit insert 12x12 mm, with angle of rotation limiter and position indicator, Multipack 20 pcs.	ZFRL12-LMA
Position indicator, Multipack 20 pcs.	Z-PI

## Electrical installation




Caution: Mains voltage!

Parallel connection of other actuators possible. Observe the performance data.



## Wire colours:

1 = blue  
2 = brown  
3 = white

AC 230 V, open/close



AC 230 V, 3-point



## Dimensions

## Spindle length

