

Linear actuator for adjusting dampers and slide valves in technical building installations

- Air damper size up to approx. 3 m²
- Actuating force 450 N
- Nominal voltage AC 100...240 V
- Control Open/close, 3-point
- Length of Stroke Max. 100 mm, adjustable in 20 mm increments



Picture may differ from product

Technical data

Electrical data	
	Nominal voltage
	AC 100...240 V
	Nominal voltage frequency
	50/60 Hz
	Nominal voltage range
	AC 85...265 V
	Power consumption in operation
	3 W
	Power consumption in rest position
	0.6 W
	Power consumption for wire sizing
	7 VA
	Connection supply / control
	Cable 1 m, 3x 0.75 mm ²
	Parallel operation
	Yes (note the performance data)
Functional data	
	Actuating force motor
	450 N
	Direction of motion motor
	selectable with switch 0 (extended) / 1 (retracted)
	Manual override
	with push-button, can be locked
	Stroke
	100 mm
	Length of Stroke
	Max. 100 mm, adjustable in 20 mm increments
	Stroke limitation
	can be limited on both sides with mechanical end stops
	Running time motor
	150 s / 100 mm
	Sound power level, motor
	52 dB(A)
Safety data	
	Protection class IEC/EN
	II, reinforced insulation
	Protection class UL
	II, reinforced insulation
	Degree of protection IEC/EN
	IP54
	Degree of protection NEMA/UL
	NEMA 2
	Housing
	UL Enclosure Type 2
	EMC
	CE according to 2014/30/EU
	Low voltage directive
	CE according to 2014/35/EU
	Certification IEC/EN
	IEC/EN 60730-1 and IEC/EN 60730-2-14
	UL Approval
	cULus according to UL60730-1A, UL60730-2-14 and CAN/CSA E60730-1
	The UL marking on the actuator depends on the production site, the device is UL-compliant in any case
	Hygiene test
	According to VDI 6022 Part 1 / SWKI VA 104-01, cleanable and disinfectable, low emission
	Type of action
	Type 1

Safety data	Rated impulse voltage supply / control	4 kV
Pollution degree		3
Ambient humidity		Max. 95% RH, non-condensing
Ambient temperature		-30...50°C [-22...122°F]
Storage temperature		-40...80°C [-40...176°F]
Servicing		maintenance-free
Weight	Weight	1.1 kg

Safety notes



- This device has been designed for use in stationary heating, ventilation and air-conditioning systems and must not be used outside the specified field of application, especially in aircraft or in any other airborne means of transport.
- Outdoor application: only possible in case that no (sea) water, snow, ice, insolation or aggressive gases interfere directly with the device and that it is ensured that the ambient conditions remain within the thresholds according to the data sheet at any time.
- Caution: Mains voltage!
- Only authorised specialists may carry out installation. All applicable legal or institutional installation regulations must be complied with during installation.
- The device may only be opened at the manufacturer's site. It does not contain any parts that can be replaced or repaired by the user.
- The rotary supports and coupling pieces available as accessories must always be used if transverse forces are likely. In addition, the actuator must not be tightly bolted to the application. It must remain movable via the rotary support (refer to «Installation notes»).
- If the actuator is exposed to severely contaminated ambient air, appropriate precautions must be taken on the system side. Excessive deposits of dust, soot etc. can prevent the gear rod from being extended and retracted correctly.
- If not installed horizontally, the manual override button may only be actuated when there is no pressure on the gear rod.
- To calculate the actuating force required for air dampers and slide valves, the specifications supplied by the damper manufacturers concerning the cross- section and the design, as well as the installation situation and the ventilation conditions must be observed.
- If a rotary support and/or coupling piece is used, actuation force losses are to be expected.
- The device contains electrical and electronic components and must not be disposed of as household refuse. All locally valid regulations and requirements must be observed.

Product features

Simple direct mounting	The actuator can be directly connected with the application using the enclosed screws. The head of the gear rod is connected to the moving part of the ventilating application individually on the mounting side or with the Z-KS1 coupling piece provided for this purpose.
Manual override	Manual override with push-button possible (the gear train is disengaged for as long as the button is pressed or remains locked).
Adjustable stroke	If a stroke limitation will be adjusted, the operating range on this side of the gear rod can be used starting with an extension length of 20 mm and then can be limited respectively in increments of 20 mm by means of the mechanical end stops Z-AS1.
High functional reliability	The actuator is overload protected, requires no limit switches and automatically stops when the end stop is reached.

Accessories

Mechanical accessories	Description	Type
	End stop kit, Multipack 20 pcs.	Z-AS1

Accessories

Description

Type

Coupling piece M8	Z-KS1
Rotary support, for linear actuator, for compensation of transverse forces	Z-DS1


Electrical installation

**Caution: Mains voltage!****Parallel connection of other actuators possible. Observe the performance data.**



Wire colours:

1 = blue
2 = brown
3 = white

AC 230 V, open/close



AC 230 V, 3-point



Installation notes

**If a rotary support and/or coupling piece is used, losses in the actuation force losses are to be expected.**

Applications without transverse forces

The linear actuator is screwed directly to the housing at three points. Afterwards, the head of the gear rod is fastened to the moving part of the ventilation application (e.g. damper or slide valve).

Applications with transverse forces

The coupling piece with the internal thread (Z-KS1) is connected to the head of the gear rod. The rotary support (Z-DS1) is screwed to the ventilation application. Afterwards, the linear actuator is screwed to the previously mounted rotary support with the enclosed screw. Afterwards, the coupling piece, which is mounted to the head of the gear rod, is attached to the moving part of the ventilating application (e.g. damper or slide valve). The transverse forces can be compensated for to a certain limit with the rotary support and/or coupling piece. The maximum permissible swivel angle of the rotary support and coupling piece is 10° (angle), laterally and upwards.

Stroke limitation

If the stroke limitations are used on the gear rod, the mechanical operating range on this side of the gear rod can be used starting with an extension length of 20 mm.

Dimensions

