

Damper actuator for adjusting dampers in technical building installations

- Air damper size up to approx. 4 m<sup>2</sup>
- Torque motor 20 Nm
- Nominal voltage AC 100...240 V
- Control Open/close, 3-point
- with integrated auxiliary switch



Picture may differ from product

## Technical data

Electrical data	Nominal voltage	AC 100...240 V
	Nominal voltage frequency	50/60 Hz
	Nominal voltage range	AC 85...265 V
	Power consumption in operation	2.5 W
	Power consumption in rest position	0.6 W
	Power consumption for wire sizing	6 VA
	Auxiliary switch	1x SPDT, 0...100%
	Switching capacity auxiliary switch	1 mA...3 A (0.5 A inductive), DC 5 V...AC 250 V
	Connection supply / control	Cable 1 m, 3x 0.75 mm <sup>2</sup>
	Connection auxiliary switch	Cable 1 m, 3x 0.75 mm <sup>2</sup>
	Parallel operation	Yes (note the performance data)
Functional data	Torque motor	20 Nm
	Direction of motion motor	selectable with switch 0 (ccw rotation) / 1 (cw rotation)
	Manual override	with push-button, can be locked
	Angle of rotation	Max. 95°
	Angle of rotation note	can be limited on both sides with adjustable mechanical end stops
	Running time motor	150 s / 90°
	Sound power level, motor	45 dB(A)
	Mechanical interface	Universal shaft clamp reversible 10...20 mm
	Position indication	Mechanical, pluggable
Safety data	Protection class IEC/EN	II, reinforced insulation
	Protection class UL	II, reinforced insulation
	Protection class auxiliary switch IEC/EN	II, reinforced insulation
	Degree of protection IEC/EN	IP54
	Degree of protection NEMA/UL	NEMA 2
	Housing	UL Enclosure Type 2
	EMC	CE according to 2014/30/EU
	Low voltage directive	CE according to 2014/35/EU
	Certification IEC/EN	IEC/EN 60730-1 and IEC/EN 60730-2-14

<b>Safety data</b>	UL Approval	cULus according to UL60730-1A, UL60730-2-14 and CAN/CSA E60730-1 The UL marking on the actuator depends on the production site, the device is UL-compliant in any case
Hygiene test		According to VDI 6022 Part 1 / SWKI VA 104-01, cleanable and disinfectable, low emission
Type of action	Type 1.B	
Rated impulse voltage supply / control	2.5 kV	
Rated impulse voltage auxiliary switch	2.5 kV	
Pollution degree	3	
Ambient humidity	Max. 95% RH, non-condensing	
Ambient temperature	-30...50°C [-22...122°F]	
Storage temperature	-40...80°C [-40...176°F]	
Servicing	maintenance-free	
<b>Weight</b>	Weight	1.1 kg

## Safety notes



- This device has been designed for use in stationary heating, ventilation and air-conditioning systems and must not be used outside the specified field of application, especially in aircraft or in any other airborne means of transport.
- Outdoor application: only possible in case that no (sea) water, snow, ice, insolation or aggressive gases interfere directly with the device and that it is ensured that the ambient conditions remain within the thresholds according to the data sheet at any time.
- Caution: Mains voltage!
- Only authorised specialists may carry out installation. All applicable legal or institutional installation regulations must be complied with during installation.
- The device may only be opened at the manufacturer's site. It does not contain any parts that can be replaced or repaired by the user.
- Cables must not be removed from the device.
- To calculate the torque required, the specifications supplied by the damper manufacturers concerning the cross-section and the design, as well as the installation situation and the ventilation conditions must be observed.
- The device contains electrical and electronic components and must not be disposed of as household refuse. All locally valid regulations and requirements must be observed.

## Product features

<b>Simple direct mounting</b>	Simple direct mounting on the damper shaft with a universal shaft clamp, supplied with an anti-rotation mechanism to prevent the actuator from rotating.
<b>Manual override</b>	Manual override with push-button possible (the gear train is disengaged for as long as the button is pressed or remains locked).
<b>Adjustable angle of rotation</b>	Adjustable angle of rotation with mechanical end stops.
<b>High functional reliability</b>	The actuator is overload protected, requires no limit switches and automatically stops when the end stop is reached.
<b>Flexible signalling</b>	With adjustable auxiliary switch (0...100%)

## Accessories

Electrical accessories	Description	Type
Auxiliary switch 1x SPDT add-on		S1A
Auxiliary switch 2x SPDT add-on		S2A
Feedback potentiometer 140 $\Omega$ add-on		P140A
Feedback potentiometer 1 k $\Omega$ add-on		P1000A
Feedback potentiometer 10 k $\Omega$ add-on		P10000A
Mechanical accessories	Description	Type
Actuator arm for standard shaft clamp (reversible)		AH-20
Shaft extension 240 mm $\varnothing$ 20 mm for damper shaft $\varnothing$ 12...21 mm CrNi		AV12-25-I
Shaft extension 240 mm $\varnothing$ 20 mm for damper shaft $\varnothing$ 8...22.7 mm		AV8-25
Ball joint suitable for damper crank arm KH8		KG8
Ball joint suitable for damper crank arm KH8 / KH10		KG10A
Damper crank arm Slot width 8.2 mm, clamping range $\varnothing$ 10...18 mm		KH8
Shaft clamp one-sided, clamping range $\varnothing$ 8...26 mm, Multipack 20 pcs.		K-ENSA
Shaft clamp one-sided, clamping range $\varnothing$ 12...26 mm, for CrNi shaft (INOX), Multipack 20 pcs.		K-ENSA-I
Shaft clamp reversible, clamping range $\varnothing$ 10...20 mm		K-SA
Anti-rotation mechanism 180 mm, Multipack 20 pcs.		Z-ARS180
Anti-rotation mechanism 230 mm, Multipack 20 pcs.		Z-ARS230
Form fit insert 10x10 mm, Multipack 20 pcs.		ZF10-NSA
Form fit insert 12x12 mm, Multipack 20 pcs.		ZF12-NSA
Form fit insert 15x15 mm, Multipack 20 pcs.		ZF15-NSA
Form fit insert 16x16 mm, Multipack 20 pcs.		ZF16-NSA
Mounting kit for linkage operation for flat installation		ZG-SMA
Position indicator, Multipack 20 pcs.		Z-PI
Baseplate extension for SM..A to SM../AM../SMD24R		Z-SMA

## Electrical installation




Caution: Mains voltage!

Parallel connection of other actuators possible. Observe the performance data.


## Wire colours:

1 = blue  
 2 = brown  
 3 = white  
 S1 = violet  
 S2 = red  
 S3 = white



AC 230 V, open/close




AC 230 V, 3-point



Auxiliary switch



## Operating controls and indicators



## Auxiliary switch settings

**Note:** Perform settings on the actuator only in deenergised state.

For the auxiliary switch position settings, carry out points ① to ④ successively.

## ① Manual override button

Holding button pressed down: Gear train disengages.  
Manual override is possible.

## ② Shaft clamp

Turn until edge line A displays the desired switching position of the actuator and release button ①.

## ③ Auxiliary switch

Turn rotary knob until the arrow points to the vertical line.


## ④ Cable

Connect continuity tester to S1 + S2 or to S1 + S3.  
If the auxiliary switch should switch in the opposite direction, rotate the auxiliary switch by 180°.

## Dimensions


## Spindle length

	Min. 48
	Min. 20 mm [0.75"]



## Clamping range

	10...20	$\geq 10$	$\leq 20$
CrNi (INOX)	12...20	$\geq 10$	$\leq 20$



When using a round shaft made of CrNi (INOX):  $\varnothing 12 \dots 20$  mm