



Technical data

Electrical data	Electrical Connection	18 GA plenum cable, 1 m
Functional data	Shaft Diameter	1" round
Safety data	UL 2043 Compliant	Suitable for use in air plenums per Section 300.22(C) of the NEC and Section 602 of the IMC
	Ambient temperature	-29...129°F [-34...54°C]
	Storage temperature	-40...176°F [-40...80°C]
	Servicing	maintenance-free
Weight	Weight	0.70 lb [0.30 kg]
Materials	Housing material	UL94V-0

Product features

- Application** The P475-1 damper position switch is used to indicate when a desired position of a damper is reached or to interface additional control for a specific control sequence.
- Operation** The P475-1 is mounted onto the damper shaft. This switch uses a roller ball and mechanical switch to provide open/close/operating damper position status. The P475-1 offers a non-mercury alternative for applications and for projects which do not allow mercury.

Accessories


Mechanical accessories	Description	Type
		F6150HD

Electrical installation

- Warning! Live electrical components!** During installation, testing, servicing and troubleshooting of this product, it may be necessary to work with live electrical components. Have a qualified licensed electrician or other individual who has been properly trained in handling live electrical components perform these tasks. Failure to follow all electrical safety precautions when exposed to live electrical components could result in death or serious injury.
- INSTALLATION NOTES**
- Provide overload protection and disconnect as required.

Wiring diagrams

P475(-1)



Dimensions

